

MULTIMEDIA PROJECTOR

## **D966HD**



## High Brightness 1080p Multimedia Projector

The Vivitek D966HD is a high brightness 1080p multimedia digital projector. The D966HD delivers a amazing image quality and would be perfectly suited for large meeting rooms thanks its 4200 ANSI Lumens of brightness and an outstanding contrast ratio of 10.000:1. The D966HD offers also exceptional color saturation.

## **Features**

- Native 1080p (1920 x 1080) resolution with display up to WUXGA(1920 x 1200)
- High Brightness of 4200 ANSI lumens and high 10,000:1 Contrast ratio ensuring a crisp and sharp image
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, DisplayPort)
- New efficient lamp offering up to 4,000 hours of life
- Direct 3D through HDMI
- VGA—output for display on a secondary monitor
- Built-in 5W loudspeaker
- 12V trigger for connection to an external module or screen
- Network ready for integration and system administration via RJ45
- Crestron® RoomView™ certified
- Top-loading, sliding cover for quick and easy lamp replacement
- Security solutions include: Kensington® security slot, security bar, keypad lock

Specifications	
Brightness	4200 ANSI Lumen
Native Resolution	1080p (1920 x 1080)
Max. Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	10,000:1
Lamp Life and Type	2,500/3,500/4,000h (Normal/Eco/Dynamic Eco Mode), 310W
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.6 -1.92:1 (Distance/Width)
Image Size (Diagonal)	30" to 300"
Projection Distance	1 - 10 m
Projection Lens	F=2.5, f=23.5-28.2mm
Zoom Ratio	1.2x
Aspect Ratio	16:9 Native, 4:3 & 16:10 Compatible
Offset (full image height)	115%
Keystone Correction	±40º Vertical
Speaker	5 W (SPL)
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (x2), HDMI v.1.4 (x2), DisplayPort, S-Video, Composite Video, Audio-In, (RCA), Audio-In (Mini-Jack) VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, 12vTrigger, RS-232, 3D- Sync Out, USB Service only
Security	Kensington® Lock Port
Weight	3.5 Kg
Dimensions (W x D x H)	333 x 255x 113 mm
Noise Level	40dB/35dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 370W/300W (Normal/Eco Mode) <0.5W (Standby Mode)
Warranty	Standard: 3 year warranty on projector, 1 year or 1,000 hrs on lamp
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp
UPC	814964 338945













